

Wall Mounting Watertight Metal Enclosures



IP 65 (IEC 529)



Optional Items



- * Transparent Door / Inner Door
- * Fan / Filter Ventilation



- * Modular Chassis



- * Rain Hood (outdoor)



- * Canopy (outdoor)



- * Plinth (100mm/200mmH)



- A. PVC lock (CVS standard)
- B. Metal cam lock with keys
- C. Die cast quarter turn

- * A continuous seal of polyurethane gasket at door provide high IP protection.
- * Surface finished with polyester powder coating RAL7032 texture, CVS beige colour.
- * Galvanised mounting plate and wall mounting bracket.
- * 4 welded studs for fixing mounting plate.
- * Conceal hinges provide 130° door opening.
- * Earthing facilities on door, body and mounting plate.
- * Double folded gutter at door frame increases rigidity and prevents water from entering while door is opened



SIRIM
Certified to: MS IEC 60529: 2005
Certification No.: LC020801



CERT NO. K1 R 0403479

Wall Mounting Watertight Metal Enclosures

Vertical Type

NO.	MODEL	DIMENSION (MM) H x W x D	MOUNTING PLATE (MM)	GLAND PLATE	NOS. OF LOCK	TRANS. DOOR	INNER DOOR	MOD. CHASSIS	FILTER/ R. HOOD	CANOPY	PLINTH
1	CR 252010	250 x 200 x 100	214 x 150	0	1						
2	CR 252015	250 x 200 x 150	214 x 150	0	1					•	
3	CR 302515	300 x 250 x 150	264 x 200	A1	1	•		•		•	•
4	CR 302520	300 x 250 x 200	264 x 200	A1	1	•		•	•	•	•
5	CR 303015	300 x 300 x 150	264 x 250	A1	1	•				•	•
6	CR 303020	300 x 300 x 200	264 x 250	A1	1	•			•	•	•
7	CR 403015	400 x 300 x 150	364 x 250	A1	1	•		•		•	•
8	CR 403020	400 x 300 x 200	364 x 250	A1	1	•	•	•	•	•	•
9	CR 404020	400 x 400 x 200	364 x 350	B1	1	•	•		•	•	•
10	CR 504015	500 x 400 x 150	464 x 350	A1	1	•		•		•	•
11	CR 504020	500 x 400 x 200	464 x 350	B1	1	•	•	•	•	•	•
12	CR 504025	500 x 400 x 250	464 x 350	B1	1	•	•		•	•	•
13	CR 504030	500 x 400 x 300	464 x 350	B1	1	•	•		•	•	•
14	CR 505020	500 x 500 x 200	464 x 450	B1	1	•	•		•	•	•
15	CR 505025	500 x 500 x 250	464 x 450	C1	1	•	•		•	•	•
16	CR 604015	600 x 400 x 150	564 x 350	A2	2	•		•		•	•
17	CR 604020	600 x 400 x 200	564 x 350	B2	2	•	•	•	•	•	•
18	CR 604025	600 x 400 x 250	564 x 350	B2	2	•	•	•	•	•	•
19	CR 605020	600 x 500 x 200	564 x 450	B2	2	•	•	•	•	•	•
20	CR 605025	600 x 500 x 250	564 x 450	C2	2	•	•		•	•	•
21	CR 606020	600 x 600 x 200	564 x 550	C2	2	•	•		•	•	•
22	CR 606025	600 x 600 x 250	564 x 550	C2	2	•	•		•	•	•
23	CR 606030	600 x 600 x 300	564 x 550	C2	2	•	•		•	•	•
24	CR 705020	700 x 500 x 200	664 x 450	B2	2	•	•	•	•	•	•
25	CR 705025	700 x 500 x 250	664 x 450	C2	2	•	•		•	•	•
26	CR 806020	800 x 600 x 200	764 x 550	C2	2	•	•	•	•	•	•
27	CR 806025	800 x 600 x 250	764 x 550	C2	2	•	•		•	•	•
28	CR 806030	800 x 600 x 300	764 x 550	C2	2	•	•		•	•	•
29	CR 808025	800 x 800 x 250	764 x 750	C4	2	•	•		•	•	•
30	CR 1006030	1000 x 600 x 300	964 x 550	C2	2	•	•		•	•	•
31	CR 1008030	1000 x 800 x 300	964 x 750	C4	2	•	•		•	•	•
32	CR 1208030	1200 x 800 x 300	1164 x 750	C4	2	•	•		•	•	•

Horizontal Type

1	CR302515H	250 x 300 x 150	214 x 250	A1	1	•				•	•
2	CR302520H	250 x 300 x 200	214 x 250	A1	1	•			•	•	•
3	CR403015H	300 x 400 x 150	264 x 350	A1	1	•				•	•
4	CR403020H	300 x 400 x 200	264 x 350	B1	1	•			•	•	•
5	CR504015H	400 x 500 x 150	364 x 450	A1	1	•					
6	CR504020H	400 x 500 x 200	364 x 450	B1	1	•			•	•	•
7	CR504025H	400 x 500 x 250	364 x 450	B1	1	•			•	•	•
8	CR604015H	400 x 600 x 150	364 x 550	A2	1	•					
9	CR604020H	400 x 600 x 200	364 x 550	B2	1	•			•	•	•
10	CR605020H	500 x 600 x 200	464 x 550	B2	2	•			•	•	•
11	CR605025H	500 x 600 x 250	464 x 550	C2	2	•			•	•	•
12	CR705020H	500 x 700 x 200	464 x 650	B2	2	•			•		
13	CR705025H	500 x 700 x 250	464 x 650	C2	2	•			•		

Two-Door Type*

1	CR1008030H	800 x 1000 x 300	719 x 916	C2	1	•	•			•	•
2	CR10010030	1000 x 1000 x 300	916 x 916	C2	1	•	•			•	•
3	CR12010030	1200 x 1000 x 300	1116 x 916	C2	1	•	•			•	•

Dimension for gland hole - A-174 x 60, B-259 x 88, C-310 x 115.

* IP55



SIRIM
Certified to: MS IEC 60529:2005
Certification No.: LC020801



CERT NO. KLR 0403479